



# Material Safety Data Sheet

MSDS ID NO.: 0101SPE012  
Revision date: 02/05/2004

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

**Product code:** SW07  
**Product name:** SSA Speedway SAE 30 Motor Oil  
**Synonyms:** Speedway HD 30 Motor Oil; Speedway SAE 30 Motor Oil  
**Chemical Family:** Motor/Lube Oil  
**Formula:** Mixture

**Supplier:**  
Speedway/Superamerica LLC  
P O BOX 1500  
ENON OH 45501

**Other information:** 419-421-3070  
**Emergency telephone number:** 877-627-5463

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

Motor oil is a complex mixture of highly refined lubricating oil base stocks and additives.

### Product information

Name	CAS Number	Weight %	ACGIH Exposure Limits:	OSHA - Vacated PELs - Time Weighted Ave	Other:
SSA Speedway SAE 30 Motor Oil	Mixture	100			

### Component Information

Name	CAS Number	Weight %	ACGIH Exposure Limits:	OSHA - Vacated PELs - Time Weighted Ave	Other:
Petroleum Distillates, Solvent Dewaxed Heavy Paraffinic	64742-65-0	84-94			Mineral Oil Mist (MOM) =5 mg/m <sup>3</sup> TWA = 10 mg/m <sup>3</sup> STEL
Additives	Not specified	6-16			
Zinc Alkyl Dithiophosphate	68649-42-3	0.6-1.2			

**Notes:** The manufacturer has voluntarily elected to reflect exposure limits contained in OSHA's 1989 air contaminants standard in its MSDS's, even though certain of those exposure limits were vacated in 1992.

## 3. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

MOTOR OIL IS A NON-VOLATILE AND NON-COMBUSTIBLE, AMBER COLORED LIQUID, BUT WILL IGNITE AND BURN AT ELEVATED TEMPERATURES.

**OSHA WARNING LABEL:**

**THIS PRODUCT HAS BEEN EVALUATED AND DOES NOT REQUIRE ANY HAZARD WARNING LABEL UNDER THE OSHA HAZARD COMMUNICATION STANDARD.**

**CONSUMER WARNING LABEL:**

**A CONSUMER WARNING LABEL IS NOT APPLICABLE FOR THIS PRODUCT.**

**Inhalation:** No acute effects expected from routine operations. Overheating of product may produce vapors which can cause respiratory irritation, dizziness and nausea.

**Ingestion:** Product has a low order of acute toxicity. This is based on data from components or similar products.

**Skin contact:** Prolonged and repeated liquid contact can cause dermatitis, folliculitis or oil acne.

**Eye contact:** Liquid or vapor contact may result in slight eye irritation.

**Carcinogenic Evaluation:**

**Product information**

Name	IARC:	NTP:	ACGIH - Carcinogens:	OSHA - Select Carcinogens:
SSA Speedway SAE 30 Motor Oil Mixture	NE			

**Notes:** The International Agency for Research on Cancer (IARC) has determined that there is no evidence that severely solvent-refined oils are carcinogenic to experimental animals.

**Component Information**

**4. FIRST AID MEASURES**

**Inhalation:** If affected, move person to fresh air. If breathing is difficult, administer oxygen. If not breathing or if no heartbeat, give artificial respiration or cardiopulmonary resuscitation (CPR). If symptoms or irritation occur with any exposure, call a physician.

**Skin contact:** Wash with soap and large amounts of water. Remove contaminated clothing. If symptoms or irritation occur, call a physician.

If product is accidentally injected into or under the skin, regardless of wound size or initial absence of symptoms, the individual should be evaluated immediately by a physician as a surgical emergency.

**Ingestion:** Not expected to be acutely toxic. If large amounts are swallowed, immediately call a physician.

**Eye contact:** Flush eyes with large amounts of tepid water for at least 15 minutes. If symptoms or irritation occur, call a physician.

**Notes to physician:** High velocity injection under the skin may result in serious injury. If left untreated the affected area is subject to infection, disfigurement, lack of blood circulation and may require amputation. When dispensed by high pressure equipment this material can easily penetrate the skin and leave a bloodless puncture wound. Material injected into a finger can be deposited into the palm of the hand. Within 24-48 hours the patient may experience swelling, discoloration, and throbbing pain in the affected area. Immediate treatment by a surgical specialist is recommended.

**Medical conditions aggravated by exposure:** Skin contact could aggravate an existing skin disorder or dermatitis condition.

## 5. FIRE FIGHTING MEASURES

<b>Suitable extinguishing media:</b>	For small fires, Class B fire extinguishing media such as CO <sub>2</sub> , dry chemical, foam (AFFF/ATC) or water spray can be used. For large fires, water spray, fog or foam (AFFF/ATC) can be used. Fire fighting should be attempted only by those who are adequately trained and equipped with proper protective equipment.
<b>Specific hazards:</b>	This material is not combustible per the OSHA Hazard Communication Standard, but will ignite and burn at elevated temperatures.
<b>Special protective equipment for firefighters:</b>	Avoid using straight water streams. Water spray and foam (AFFF/ATC) must be applied carefully to avoid frothing and from as far a distance as possible. Avoid excessive water spray application. Use water spray to cool exposed surfaces from as far a distance as possible.
<b>Flash point:</b>	>400 F, >204.5 C
<b>Autoignition temperature:</b>	No data available.
<b>Flammable limits in air - lower (%):</b>	Not applicable.
<b>Flammable limits in air - upper (%):</b>	Not applicable.
<b>NFPA rating:</b>	<b>HMS classification:</b>
Health: 1	Health: 1
Flammability: 1	Flammability: 1
Reactivity: 0	Reactivity: 0
Other: -	Special: *See Section 8 for guidance in selection of personal protective equipment.

## 6. ACCIDENTAL RELEASE MEASURES

<b>Personal precautions:</b>	Keep public away. Isolate and evacuate area. Shut off source if safe to do so. Advise authorities and National Response Center (800-424-8802) if substance has entered a watercourse or sewer. Contain liquid with sand or soil. Recover and return free product to proper containers. Use suitable absorbent materials such as vermiculite, sand, or clay to clean up residual liquids.
------------------------------	--

## 7. HANDLING AND STORAGE

**Handling:**  
Comply with all applicable EPA, OSHA, NFPA and consistent state and local requirements. Use appropriate grounding and bonding practices. Store in properly closed containers that are appropriately labeled and in a cool well-ventilated area. Do not cut, drill, grind or weld on empty containers since they may contain explosive residues. Do not pressurize or expose to heat, open flames, strong oxidizers or other sources of ignition.

Avoid repeated and prolonged skin contact. Exercise good personal hygiene including removal of soiled clothing and prompt washing with soap and water.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### PERSONAL PROTECTIVE EQUIPMENT

<b>Engineering measures:</b>	Local or general exhaust required when using at elevated temperatures that generate vapors or mists.
------------------------------	--

<b>Respiratory protection:</b>	Not required under normal conditions and adequate ventilation. Approved organic vapor chemical cartridge or supplied air respirators should be worn when significant vapors are generated. Observe respirator protection factor criteria cited in ANSI Z88.2. Self-contained breathing apparatus should be used for fire fighting.
<b>Skin and body protection:</b>	Use chemical resistant gloves such as neoprene, nitrile, or PVA to prevent prolonged or repeated skin contact.
<b>Eye protection:</b>	No special eye protection is normally required.
<b>Hygiene measures:</b>	No data available.

## 9. PHYSICAL AND CHEMICAL PROPERTIES:

<b>Appearance:</b>	Amber Liquid
<b>Physical state (Solid/Liquid/Gas):</b>	Liquid
<b>Substance type (Pure/Mixture):</b>	Mixture
<b>Color:</b>	Amber
<b>Odor:</b>	Hydrocarbon
<b>Molecular weight:</b>	Not determined.
<b>pH:</b>	Neutral
<b>Boiling point/range:</b>	No data available.
<b>Melting point/range:</b>	No data available.
<b>Decomposition temperature:</b>	Not applicable.
<b>Specific gravity:</b>	0.90 @ 60 F
<b>Density:</b>	7.41 lbs/gallon @ 60 F
<b>Bulk density:</b>	No data available.
<b>Vapor density:</b>	No data available.
<b>Vapor pressure:</b>	< 1 mm Hg @ 100 F
<b>Evaporation rate:</b>	No data available.
<b>Solubility:</b>	Slight <1%
<b>Solubility in other solvents:</b>	No data available.
<b>Partition coefficient (n-octanol/water):</b>	>4.9
<b>VOC content(%):</b>	No data available.
<b>Viscosity:</b>	10.0 - 12.0 cSt @ 100 C

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	The material is stable at 70 F, 760 mm pressure.
<b>Polymerization:</b>	Will not occur.
<b>Hazardous decomposition products:</b>	Carbon monoxide, carbon dioxide, hydrogen sulfide, oxides of sulfur, oxides of nitrogen, oxides of phosphorous, oxides of magnesium, boric oxide, calcium oxide and zinc oxide.
<b>Materials to avoid:</b>	Strong oxidizers such as nitrates, chlorates, peroxides.
<b>Conditions to avoid:</b>	No data available.

## 11. TOXICOLOGICAL INFORMATION

**Acute toxicity:**

**Product information**

Name	CAS Number	Inhalation:	Dermal:	Oral:
SSA Speedway SAE 30 Motor Oil	Mixture	LD50 = 2.14- >4 mg/l [Rat]	LD50 >2 gm/kg [Rabbit]	LD50 > 5 ml/kg [Rat]

Based on data from components this product is considered to have a low order of acute oral and dermal toxicity. Chronic skin painting studies with severely solvent refined neutral oils did not produce evidence of skin cancer in mice.

This product contains approximately 0-2.5% of a zinc alkyl dithiophosphate (ZDDP) additive. ZDDP has been found to have weak mutagenic activity in cultured cells. Repeated dermal exposures of ZDDP produced severe skin irritation, significant weight loss and testicular atrophy in male rabbits but not male rats at high concentrations. Subsequent research showed that the testicular effect was due to the severe stress and weight loss as seen with other caustic materials and not a direct effect of ZDDP. The concentration of ZDDP in this product is significantly lower than exposure levels that produced these effects in rabbits.

Use motor oil applied to the skin of rabbits at doses of 8 ml/kg/day, 5 days/wk, for two weeks, produced significant weight loss and skin irritation but no mortality. Used motor oil was found to produce skin tumors in mice in lifetime skin painting studies. Solvent extracts of used motor oils were found to be positive in the Ames mutagenicity test.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity effects:

Water accomated fractions (WAF) of highly refined base oils did not produce acute toxicity in fish (100-1000 mg/l), fresh water algae (500 mg/l) or daphnia (10,000 mg/l) in 48-96 hour LC50 studies.

Used motor and/or lube oils can be toxic to birds and fish.

## 13. DISPOSAL CONSIDERATIONS

### Cleanup Considerations:

This material as supplied and by itself, when discarded or disposed of, is not an EPA RCRA hazardous waste according to federal regulations. This material could become a hazardous waste if mixed or contaminated with a hazardous waste or other substance(s). It is the responsibility of the user to determine if disposal material is hazardous according to federal, state and local regulations.

Don't pollute. Conserve resources. Send used product to recycling center. Dispose of cleanup materials in accordance with applicable local, state and federal regulations.

## 14. TRANSPORT INFORMATION

49 CFR 172.101:

### DOT:

**Transport Information:** This material when transported via US commerce IS NOT REGULATED BY DOT regulations.

**DOT reportable quantity (lbs):** Not applicable.

### TDG (Canada):

**Regulated substances:** Not applicable.

## 15. REGULATORY INFORMATION

### Federal Regulatory Information:

MSDS ID NO.: 0101SPE012

Product name: SSA Speedway SAE 30 Motor Oil

Page 5 of 8

US TSCA Chemical Inventory Section 8(b):

This product and/or its components are listed on the TSCA Chemical Inventory.

OSHA Hazard Communication Standard:

This product has been evaluated and determined not to be hazardous as defined in OSHA's Hazard Communication Standard.

**EPA Superfund Amendment & Reauthorization Act (SARA):**

**SARA Section 302:**

This product contains the following component(s) that have been listed on EPA's Extremely Hazardous Substance (EHS) List:

Name	CERCLA/SARA - Section 302 Extremely Hazardous Substances and TPQs
Petroleum Distillates, Solvent Dewaxed Heavy Paraffinic	NA
Additives	NA
Zinc Alkyl Dithiophosphate	NA

**SARA Section 304:**

This product contains the following component(s) identified either as an EHS or a CERCLA Hazardous substance which in case of a spill or release may be subject to SARA reporting requirements:

Name	CERCLA/SARA - Hazardous Substances and their Reportable Quantities
Petroleum Distillates, Solvent Dewaxed Heavy Paraffinic	NA
Additives	NA
Zinc Alkyl Dithiophosphate	NA

**SARA Section 311/312:**

The following EPA hazard categories apply to this product:

None

**SARA Section 313:**

This product contains the following component(s) that may be subject to reporting on the Toxic Release Inventory (TRI) From R:

Name	CERCLA/SARA 313 Emission reporting:
Petroleum Distillates, Solvent Dewaxed Heavy Paraffinic	None
Additives	None
Zinc Alkyl Dithiophosphate	None

**State and Community Right-To-Know Regulations:**

The following component(s) of this material are identified on the regulatory lists below:

Petroleum Distillates, Solvent Dewaxed Heavy Paraffinic

Louisiana Right-To-Know:	Not Listed
California Proposition 65:	Not Listed
New Jersey Right-To-Know:	Not Listed.
Pennsylvania Right-To-Know:	Not Listed.
Massachusetts Right-To Know:	Not Listed.
Florida substance List:	Not Listed.
Rhode Island Right-To-Know:	Not Listed
Michigan critical materials register list:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	Not Listed
New Jersey - Environmental Hazardous Substances List:	Not Listed

Illinois - Toxic Air Contaminants	Not Listed
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	Not Listed
<b>Additives</b>	
Louisiana Right-To-Know:	Not Listed
California Proposition 65:	Not Listed
New Jersey Right-To-Know:	Not Listed.
Pennsylvania Right-To-Know:	Not Listed.
Massachusetts Right-To Know:	Not Listed.
Florida substance List:	Not Listed.
Rhode Island Right-To-Know:	Not Listed
Michigan critical materials register list:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	Not Listed
New Jersey - Environmental Hazardous Substances List:	Not Listed
Illinois - Toxic Air Contaminants	Not Listed
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	Not Listed
<b>Zinc Alkyl Dithiophosphate</b>	
Louisiana Right-To-Know:	Not Listed
California Proposition 65:	Not Listed
New Jersey Right-To-Know:	Not Listed.
Pennsylvania Right-To-Know:	Not Listed.
Massachusetts Right-To Know:	Not Listed.
Florida substance List:	Not Listed.
Rhode Island Right-To-Know:	Not Listed
Michigan critical materials register list:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	Not Listed
New Jersey - Environmental Hazardous Substances List:	Not Listed
Illinois - Toxic Air Contaminants	Not Listed
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	Not Listed

**Canadian Regulatory Information:**

Canada DSL/NDSL Inventory: This product and/or its components are listed either on the Domestic Substances List (DSL) or the Non Domestic Substance List (NDSL).

**16. OTHER INFORMATION**

**Additional Information:** No data available.

**Prepared by:** Craig M. Parker Manager, Toxicology and Product Safety

The information and recommendations contained herein are based upon tests believed to be reliable. However, Speedway SuperAmerica (SSA) does not guarantee their accuracy or completeness nor shall any of this information constitute a warranty, whether expressed or implied, as to the safety of the goods, the merchantability of the goods, or the fitness of the goods for a particular purpose. Adjustment to conform to actual conditions of usage maybe required. SSA assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.

**End of Safety Data Sheet**